

Waterman Fabricated Slide Gates-Ordering Information

Project Name:			Pro	ject Location:		Bid Date:
1	Gate Information Quantity of Gates Material: Aluminum Stainless Steel 304 Stainless Steel 316 Stainless Steel 2205		_	zing stangular	Circular Diameter	
3	Hoist Requir	ements				
	□ Manual □ Handcrank □ Handwheel	Volts Phase Cycles	□ Cylinder □ Oil □ Water □ Air □ PSI	□ Rising Stem □ Plastic Cove □ Metal Cover		□ Position Indicator □ Dial □ Mylar Strip
4	Lift Mounting Lift + Pedestal Mounted to Slab	Floorbox (flush mounted includes remove T-handle key/w	d, M vable	ft + Pedestal ounted to Bracket	☐ Mounted to Yoke or Torque Tube (Self Contained Only)	☐ Lift Mounted on Offset Pedestal
5	OPERATING FLOOR ELEVATION WATER LEVEL SEATING SIDE OPERATING HEAD INVERT ELEVATION	WATER LEVEL UNSEATING SIDE UNSEATING HEAD		/pe:	□ Cha □ Pipe	n: wnward 4 Sides adwall annel Mount (to wall) annel Mount (embedded) e Flange (type) arugated Pipe

☐ Non Self

Contained

Contained