



Electric Motor Operator Options for Ordering

Contact Information

Job Name: _____ Job number: _____

Contact Name: _____ Phone number: _____

Email Address: _____

Manufacturer Preference:

- AUMA Limitorque Rotork EIM

Service:

- Open/Close
 Moderate Modulating - 25% Duty Cycle
 Continuous Modulating - 50% Duty Cycle

Power Supply Voltage:

- 460/480 230/240 Three phase 120/110 Single phase

Power Supply Frequency:

- 60 Hertz 50 Hertz DC Voltage: _____
 Other: _____

Controls:

- Local Push Button Remote Push Button
 Remote Signal Output Remote Signal Input (4-20mA)
 Remote Signal Readout Alarm Output

Motor Operator Enclosure Type:

- Nema 7 Nema 4 IP67
 IP68 Other: _____

Motor Operator Enclosure:

- Submerged Non-Submerged

Gate Speed:

- 10-14 Inches/Minute Other _____

Handwheel Position:

- Side Top

Handwheel Direction to Open Gate:

- Clockwise / Right Hand Counter-Clockwise/Left Hand

Motor Operator Finish:

- Standard Duty Finish Corrosive Duty Finish

If you are retrofitting an existing gate, we also need the following information:

Primary Material Type: _____

Gate Size (Width, Height): _____

Fluid Head:

- Seating _____ Unseating _____
 Differential _____

Stem Length:

Distance from operator mount to thrust nut: _____

Stem Diameter: _____

Factory Start Up:

- Yes No

Seat Type (Friction Factor): _____

Seat Type:

- UHMW Bronze Metal to Metal J-Bulb

Mounting:

- Headrail Pedestal